

Middex DC Motor Drivers



DC2Q

Application	Driver for brush-type motor
Supply voltage	24VDC +/- 25%
Motor current	0...6A, momentarily 10A, current limiting
Current protection	0...6A, reaction time 1...700ms potentiometer adjustable
Inputs	Digital: right, left, signal voltage 24V (5V); Analog: rpm 0...10V
Output signal	Ready
Dimensions	Approximately 79x25x86mm (HxWxD)
Mounting/housing	DIN rail/plastic
Features	Short ramp-up motor protection, electronic current fuse, cable plug



DC2Q-AS

Application	Driver for brush-type DC motors
Supply voltage	18...30VDC, momentarily 36VDC
Motor current	0.1...5A, adjustable with pot, volt-meter output for series adjustments
Electronic fuse	0.1...5A, reaction time 1 to 700ms pot adjustable, volt-meter output for series adjustments
Inputs	Digital: right, left, signal voltage 24V (or 5V); Analog: rpm 0 - 10V
Output signals	Error, reaction time and current limit setting point
Dimensions	Approx. 101x23x120mm (HxWxD) without plugs
Mounting/housing	Cabinet wall, or OEM open
Features	Ramp-up motor protection, electronic current fuse, Rxl compensation, electronic friction clutch, cable plugs



DC4Q

Application	Driver for DC motor and Brush-less motors with Hall sensors
Supply voltage	24...48VDC, max. 52VDC
Motor current	0...6A, momentarily 20A, current limiting
Current protection	0...6A, reaction time 1...700ms potentiometer adjustable
Inputs	Digital: enable, direction, stop, max. current reduction 50%
Output signal	Ready
Dimensions	Approx. 145x36x112mm (HxWxD)
Mounting/housing	Cabinet wall, or OEM open
Features	With brake circuit, a unit for several motor types, cable plugs

Detailed data of each driver is available. Please let us know by checking the particular drive request on our web page or give us call.

All text, technical data, measurements and samples were prepared thoroughly. However Middex Electronic and CIRO Products Ltd. can not be held liable for errors and omissions. Middex Electronic and CIRO Products Ltd. reserve the right to improve or change the design of hard and software and make changes to the technical documentation without further notice.